

3400 Series Specifications

Structure	FULL PC98/PC Compliant ACPI 1.0 compliant
Processor	uPGA1 package mobile Pentium II / Celeron -> 300/333/366/400MHz
Memory	DRAM up to 256 MB (SYNC) DIMM 3.3V 144 Pin SODIMM
Display	14.4"/13.3"/12.1" TFT LCD
Video RAM	8MB SGRAM, AGP 2X 64-bit hardware 2D/3D graphic engine
CD-ROM	removable - DVD/LS-120/FDD
HDD	2.5" 9.5mm, Ultra-33 I/F supporting
Sound	3D, Full duplex Stereo speakers, mic Line-in jack/headphone jack/microphone jack
PCMCIA	1xCardBus ZV port support
Communication	FIR(IrDA 1.1)/ASKIR, HPSIR(IrDA1.0) RJ-11 jack for 56k v.90
Battery	Li-Ion/Ni-MH
Ports	serial, parallel, CRT, DC, PS2, USB, port replicator
Accessories	3405 Car Adapter 3406 port replicator 340B LS-120 3407 56k v.90 modem module 340C DVD-Rom Drive 3401S Li-Ion battery 3402D Ni-MH battery
Dimentions	306(w)x232(d)x32(h)mm 2.4kg

Chipset
Core Logic
VGA
Audio
Super I/O
PCMCIA
K/B controller
CODEC

LCD Panel
12.1
13.3
13.3
13.3
13.3
13.3

Vender	Model
Intel	440BX
ATI	Mobility-P
YAMAHA	Yamaha-744B
SMC	37N869
RICOH	Ricoh-475
HITACHI	H8
AKM	AK4543

Vender	Model
SANYO	TM121SV-02L04
LG	LP133X4-D1PC
LG	LP133X7-A2
HYUNDAI	HT3X13-203
HYUNDAI	HT3X13-213
HYUNDAI	Garnet HT13X14