

Standard CMOS Setup

ROM BIOS AWARD (25A17E9)																																																						
Standard CMOS Setup																																																						
Date (mm-dd-yy) : Mon, Jan 24 1994																																																						
Time (mm:ss) : 10:38:55																																																						
Daylight Saving : Disabled																																																						
<table border="1"> <thead> <tr> <th>HARD DISKS</th> <th>TYPE</th> <th>SIZE</th> <th>CYL</th> <th>HEAD</th> <th>PRECOMP</th> <th>LANDS</th> <th>SECTOR</th> <th>MODE</th> </tr> </thead> <tbody> <tr> <td>Primary Master</td> <td>User</td> <td>540</td> <td>1400</td> <td>16</td> <td>65536</td> <td>1400</td> <td>63</td> <td>Normal</td> </tr> <tr> <td>Primary Slave</td> <td>None</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>-----</td> </tr> <tr> <td>Secondary Master</td> <td>None</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>-----</td> </tr> <tr> <td>Secondary Slave</td> <td>None</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>-----</td> </tr> </tbody> </table>										HARD DISKS	TYPE	SIZE	CYL	HEAD	PRECOMP	LANDS	SECTOR	MODE	Primary Master	User	540	1400	16	65536	1400	63	Normal	Primary Slave	None	0	0	0	0	0	0	-----	Secondary Master	None	0	0	0	0	0	0	-----	Secondary Slave	None	0	0	0	0	0	0	-----
HARD DISKS	TYPE	SIZE	CYL	HEAD	PRECOMP	LANDS	SECTOR	MODE																																														
Primary Master	User	540	1400	16	65536	1400	63	Normal																																														
Primary Slave	None	0	0	0	0	0	0	-----																																														
Secondary Master	None	0	0	0	0	0	0	-----																																														
Secondary Slave	None	0	0	0	0	0	0	-----																																														
Drive A : 1.44M, 3.5 in.																																																						
Drive B : 1.2M, 5.25 in.																																																						
Video : EGA/VGA																																																						
Halt On : All Errors																																																						
<table border="1"> <tr> <td>ESD : Out</td> <td>1.1 - 1.2</td> <td>Select Item</td> </tr> <tr> <td>FI : Help</td> <td>(F5/F6)</td> <td>Change Color</td> </tr> </table>										ESD : Out	1.1 - 1.2	Select Item	FI : Help	(F5/F6)	Change Color																																							
ESD : Out	1.1 - 1.2	Select Item																																																				
FI : Help	(F5/F6)	Change Color																																																				
<table border="1"> <tr> <td>Base Memory:</td> <td>640K</td> </tr> <tr> <td>Extended Memory:</td> <td>7168K</td> </tr> <tr> <td>Other Memory:</td> <td>384K</td> </tr> <tr> <td>Total Memory:</td> <td>8192K</td> </tr> </table>										Base Memory:	640K	Extended Memory:	7168K	Other Memory:	384K	Total Memory:	8192K																																					
Base Memory:	640K																																																					
Extended Memory:	7168K																																																					
Other Memory:	384K																																																					
Total Memory:	8192K																																																					
PUP/D-/-: Modify																																																						

The Standard CMOS Setup screen is displayed above. Each item may have one or more option settings. The System BIOS automatically detects memory size, thus no changes are necessary. Use the arrow keys to highlight the item and then use the <PgUp> or <PgDn> keys to select the value you want in each item.

Hard Disk Configurations

TYPE :

Select from "1" to "45" to fill remaining fields with predefined values of disk drives. Select "User" to fill the remaining fields.

SIZE :

The hard disk size.

CYL :

The unit is Mega Bytes. The cylinder number of the hard disk.

HEAD :

The range is from "1" to "1024". The read/write head number of hard disk.

PRECOMP : The cylinder number at which the disk drive changes the write timing. The range is from "1" to "1024", or "None".

LANDS :

The cylinder number that the disk drive heads (read/write) are seated when the disk drive is parked. The range is from "1" to "1024".

SECTOR :

The sector number of each track defined on the hard disk. The range is from "1" to "64".

MODE :

Some hard disks support LBA Mode for data transfer. If your disk does, select "LBA". Otherwise, select "Normal".

Please refer to the IDE HDD Auto Detection section on page 4-17 for a quick configuration of new hard drives.

Daylight Saving

Enable this item to set the clock one hour in advance.

Disable it to subtract one hour when standard time begins.

After the changes are made, press <Esc> to return to main menu.